



7312 bep Bearing 2D drawings and 3D CAD models

60 mm x 130 mm x 31 mm skf 7312 bep bearing

Bearing No. 7312 bep

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.71
EAN	7316576634468
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	60MM Bore; 130MM Outside Diameter; 31MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball



YOCHI BEARING LTD

	Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7312 BEP
Weight / LBS	3.766
d	2.362 Inch 60 Millimeter
D	5.118 Inch 130 Millimeter
B	1.22 Inch 31 Millimeter
bore diameter:	60 mm
radial static load capacity:	69.5 kN
outside diameter:	130 mm
cage material:	Nylon
overall width:	31 mm
outer ring width:	31 mm
contact angle:	40 °
maximum rpm:	6000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	2 mm
radial dynamic load capacity:	95.6 kN
series:	73
d	60 mm
D	130 mm
B	31 mm
d ₁	87.25 mm
d ₂	72.6 mm

YOCHI BEARING LTD

D_1	104.8 mm
a	55 mm
$r_{1,2}$ min.	2.1 mm
$r_{3,4}$ min.	1.1 mm
d_a min.	72 mm
D_a max.	118 mm
D_b max.	123 mm
r_a max.	2 mm
r_b max.	1 mm
Basic dynamic load rating C	95.6 kN
Basic static load rating C_0	69.5 kN
Fatigue load limit P_u	3 kN
Reference speed	6300 r/min
Limiting speed	6000 r/min
Calculation factor A	0.0846
Calculation factor k_r	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	1.75 kg